

BRIDGESTONE



DL
(L5)

D-LUG



OFF-THE-ROAD TIRES



The D-LUG premium bias ply tire features an extra-deep rock service tread that provides exceptional cut resistance and stability for loader applications.

- ✓ *Extra deep tread and rugged casing for rough terrain*
- ✓ *Exceptional cut and impact resistance*
- ✓ *Shoulder protection ribs*

CATEGORY	TIRE SIZE	ARTICLE	PLY RATING	COMPOUND	TRA	AVERAGE WEIGHT	OTD (32ND)	RIM/ FLANGE	OVERALL DIAMETER (IN)	OVERALL WIDTH (IN)	STATIC LOAD RADIUS	STATIC LOADED WIDTH	MIN DUAL SPACING	REVS PER MILE
Small Tubeless	17.5-25	261173	16	D2A	L-5	480	88	14.00/1.5	55.5	17.3	25.8	18.5		372
	20.5-25	261181	16	D2A	L-5	800	100	17.00/2.0	61.3	21.6	28.1	22.4		338
	23.5-25	261203	16	D2A	L-5	1,050	111	19.50/2.5	65.9	24.3	30.7	25.4		313
	23.5-25	261211	20	D2A	L-5	1,120	111	19.50/2.5	65.9	24.3	30.7	25.4		313
Large Tubeless	26.5-25	275530	20	D2A	L-5	1,380	122	22.00/3.0	70.8	27.3	32.1	28.6		294
	29.5-25	275417	22	D2A	L-5	1,740	133	25.00/3.5	75.0	30.2	34.4	31.7		276
	29.5-25	423408	28	D2A	L-5	1,800	133	25.00/3.5	75.0	30.2	34.4	31.7		277
	29.5-29	275514	28	D2A	L-5	2,080	135	25.00/3.5	79.6	30.3	35.5	30.9		263
	35/65-33	417734	30	D2V	L-5	2,700	122	28.00/3.5	81.7	35.3	38.3	37.2		252
	35/65-33	422150	42	D2V	L-5	2,950	122	28.00/3.5	81.7	35.3	38.3	37.2		252
	40/65-39	417742	36	D2V	L-5	4,130	134	32.00/4.0	95.3	40.2	43.8	42.1		217
	41.25/70-39	422525	42	D2V	L-5	4,600	146	32.00/4.5	98.8	41.5	45.1	43.5		210
Giant Tubeless	45/65-45	419400	58	D2V	L-5	5,900	146	36.00/4.5	107.5	45.1	49.6	46.6		193
	50/65-51	427424	50	D2V	L-5	7,370	161	40.00/4.5	120.9	49.6	55.7	51.5		171
	50/65-51	417971	62	D2V	L-5	8,010	161	40.00/4.5	120.9	49.6	55.6	51.2		171
	65/65-57	424080	62	D2V	L-5	16,500	180	52.00/6.0	147.0	64.6	65.8	67.2		142

UCR: Ultra Cut Resistance