

RL-4A (E-4)

150-level radial rock tire with a unique wide, flat tread arc width to help promote long, even wear

Tire Size: 27.00R49

Available in ply ratings: **



FEATURES

- Wide, flat tread radius
- Solid centerline section

BENEFITS

- Helps provide long even treadwear
- Helps provide long wear and a smooth ride even in high torque applications

TIRE SPECS

Unit of Measure: US Metric

Rim Width & Flange	19.50-4.0	Gross Contact Area (in ²)	732.5
Min. Dual Spacing (in)	35.1	Tire Volume (gal)	529.5
Overall Width (in)	29.9	Tread Depth (1/32in)	82
Overall Diameter (in)	106.5	TMPH (2S)	350
Load Sect. & Growth (in)	33.7	TMPH (4S)	270
Static Load Radius (in)	48.5	TMPH (6S)	210
Revolutions per Mile	197		

= Estimated Data

LOADS & INFLATIONS

Unit of Measure: US Metric

30 MPH MAXIMUM SPEED OFF-THE-ROAD HAULAGE SERVICE

Pressure (PSI)	65	69(*)	73	76	80	83	87	91	94	98	102(**)
Load (Lbs)	43000	44100(*)	45400	48100	49400	50700	52000	55100	56800	58400	60000(**)

= Estimated Data